



SANS PAR

CAPE TOWN
Tel: 021-5110283 - Email: info@sanspar.co.za
JOHANNESBURG
Tel: 011-3976889 - Email: jhb@sanspar.co.za
DURBAN
Tel: 031-7002485 - Email: kzn@sanspar.co.za

UNI-FLO NYLON AND POLYPROPYLENE BALL VALVE



MATERIAL

Size Range: 15mm - 50mm
Body Material: Nylon or Polypropylene
Seat Material: PTFE
Ball: Chrome plated steel
Handle: Chrome plated steel
Ends: Screwed BSP
Pressure Rating: 16 Bar

FEATURES

- Temperature ranges -30°C to +120°C
- Pressure 1600KPA
- Nickel plated steel or brass blowout-proof stem
- Heavy duty chrome plated lever with plastic sleeve
- Triple NBR O ring seals on stem
- One piece moulded body
- Available with either Nylon or Polypropylene Body

DESCRIPTION

Tough, versatile Uni-Flo Nylon or Polypropylene Ball Valves are the ideal low cost solution for fluid control often replacing more expensive brass valves. The valves have chrome plated steel balls with nickel plated steel or brass stems. Seats are of PTFE and O rings of NBR rubber. They are ideal for water supply and irrigation as well as being resistant to hydro carbons and many chemicals. The valves are suitable for temperatures of +30°C to +120°C and pressures of 1600KPA.

DIMENSIONS

DN	L	L1	H
15	125	61	70
20	140	68	85
25	155	81	100
32	175	90	120
40	200	104	130
50	205	124	145

