#### **CAPE TOWN**

Tel: 021-5110283 - Email: info@sanspar.co.za **JOHANNESBURG** 

Tel: 011-3976889 - Email: jhb@sanspar.co.za **DURBAN** 

Tel: 031-7002485 - Email: kzn@sanspar.co.za **GQEBERHA** 

Tel: 041-4512360 - Email: salespe@effast.co.za

# **UNI-FLO POLYPROPYLENE BALL VALVE**



### **DESCRIPTION**

Uni-Flo Polypropylene Ball Valves are the ideal low cost solution for fluid control often replacing more expensive brass valves. The valves have chrome plated steel balls with nickel plated steel stems. Seats are of PTFE and O-rings of NBR rubber.

## **FEATURES**

- Temperature ranges 10°C to 60°C
- Pressure 16 Bar
- Nickel plated steel blowout-proof stem
- Heavy duty chrome plated lever with plastic sleeve
- Triple NBR O ring seals on stem
- One piece moulded body

### **MATERIAL**

Size Range: 15mm - 50mm Body Material: 30% Fibreglass

reinforced Polypropylene

Seat Material: PTFE

**Ball:** Chrome plated steel **Handle:** Chrome plated steel

Ends: Screwed BSP

Pressure Rating: 16 Bar

DIMENSIONS			
DN	L	L1	н
15	125	61	70
20	140	68	85
25	155	81	100
32	175	90	120
40	200	104	130
50	205	124	145

